

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Trade name : Fill & Fix Foam EXP  
Vaporizer : Aerosol

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Intended for general public  
Main use category : Professional use, Consumer use  
Use of the substance/mixture : Polyurethane

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

Soudal N.V. N.V.  
Everdongenlaan 18-20  
2300 Turnhout  
Belgium  
T +32 14 42 42 31 - F +32 14 42 65 14  
[sds@soudal.com](mailto:sds@soudal.com) - [www.Soudal.com](http://www.Soudal.com)

**1.4. Emergency telephone number**

Emergency number : +32 14 58 45 45 (BIG)  
24h/24h

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Respiratory sensitisation, Category 1	H334
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Reproductive toxicity, Additional category, Effects on or via lactation	H362
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity — Repeated exposure, Category 2	H373
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Hazardous to the aquatic environment — Chronic Hazard, Category 1 H410

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Suspected of causing cancer. May cause harm to breast-fed children. May cause damage to organs through prolonged or repeated exposure. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Very toxic to aquatic life with long lasting effects.

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: polymethylene polyphenyl isocyanate, alkanes, C14-17, chloro

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 - May cause respiratory irritation.  
H351 - Suspected of causing cancer.  
H362 - May cause harm to breast-fed children.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H410 - Very toxic to aquatic life with long lasting effects.  
Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P308+P313 - IF exposed or concerned: Get medical advice/attention.  
P405 - Store locked up.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.  
Extra phrases : Persons already sensitised to diisocyanates may develop allergic reactions when using this product.  
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.  
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.  
As from 24 August 2023 adequate training is required before industrial or professional use.

Extra phrases

## 2.3. Other hazards

Contains PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
alkanes, C14-17, chloro substance listed as REACH Candidate (Medium-chain chlorinated paraffins (MCCP) (UVCB substances consisting of more than or equal to 80% linear chloroalkanes with carbon chain lengths within the range from C14 to C17)) PBT substance; vPvB substance	CAS-No.: 85535-85-9 EC-No.: 287-477-0 EC Index-No.: 602-095-00-X REACH-no: 01-2119519269-33	≥ 25 – < 50	Lact., H362 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)
polymethylene polyphenyl isocyanate substance with national workplace exposure limit(s) (GB)	CAS-No.: 9016-87-9	≥ 10 – < 25	Carc. 2, H351 Resp. Sens. 1, H334 Skin Sens. 1, H317 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
isobutane (Propellant gas (Aerosol))	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395-27	≥ 10 – < 25	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
dimethyl ether (Propellant gas (Aerosol))	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128-37	≥ 5 – < 10	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
propane (Propellant gas (Aerosol))	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	≥ 5 – < 10	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
alkanes, C14-17, chloro	CAS-No.: 85535-85-9 EC-No.: 287-477-0 EC Index-No.: 602-095-00-X REACH-no: 01-2119519269-33	( 0.25 ≤ C < 30) Aquatic Chronic 4, H413 ( 1 ≤ C < 100) Lact., H362 ( 1 ≤ C < 30) EUH066

Comments : polymethylene polyphenyl isocyanate, contains > 0.1% MDI isomers  
Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.  
Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: None known.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
----------------------	--

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Leave the product to solidify. Mechanically recover the product. Carefully collect the spill/leftovers. Wash clothing and equipment after handling. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact during pregnancy/while nursing. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Incompatible products : Heat sources. Ignition sources. Strong bases. Strong acids.
- Maximum storage period : 1 year
- Packaging materials : Aerosol.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

dimethyl ether (115-10-6)	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Dimethylether
IOEL TWA	1920 mg/m <sup>3</sup>
IOEL TWA [ppm]	1000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Dimethyl ether
WEL TWA (OEL TWA) [1]	766 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	958 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>polymethylene polyphenyl isocyanate (9016-87-9)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	0.02 mg/m <sup>3</sup>
WEL STEL (OEL STEL)	0.07 mg/m <sup>3</sup>

##### 8.1.2. Recommended monitoring procedures

No additional information available

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

alkanes, C14-17, chloro (85535-85-9)	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	47.9 mg/kg bw/day
Long-term - systemic effects, inhalation	6.7 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	0.58 mg/kg bw/day
Long-term - systemic effects, inhalation	2 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	28.75 mg/kg bw/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	1 µg/l
PNEC aqua (marine water)	0.2 µg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	13 mg/kg dwt
PNEC sediment (marine water)	2.6 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	11.9 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	10 mg/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	80 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosols.
Colour	: Variable.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.969 (20°C)
Density	: 969.3 kg/m <sup>3</sup> (20°C)
Solubility	: Insoluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content : 18.16 – 25.49 % (176.02 g/l - 247.03 g/l)

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Polymerisation risk. Reacts with (some) acids/bases.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### dimethyl ether (115-10-6)

LC50 Inhalation - Rat [ppm] 164000 ppm (4 h, Rat, Male, Experimental value, Inhalation (gases), 14 day(s))

#### propane (74-98-6)

LC50 Inhalation - Rat [ppm] > 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))

#### isobutane (75-28-5)

LC50 Inhalation - Rat [ppm] > 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))

#### polymethylene polyphenyl isocyanate (9016-87-9)

LD50 oral rat > 10000 mg/kg (Rat, Literature study, Oral)

LD50 dermal rabbit > 5000 mg/kg (Rabbit, Literature study, Dermal)

#### alkanes, C14-17, chloro (85535-85-9)

LD50 oral rat > 4000 mg/kg bodyweight (Rat, Male / female, Experimental value, Oral, 14 day(s))

LD50 dermal rabbit > 13500 mg/kg bodyweight (24 h, Rabbit, Read-across, Dermal)

LC50 Inhalation - Rat > 48.17 mg/l air (1 h, Rat, Read-across, Inhalation (vapours))

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Suspected of causing cancer.

#### polymethylene polyphenyl isocyanate (9016-87-9)

IARC group 3 - Not classifiable

Reproductive toxicity : May cause harm to breast-fed children.  
STOT-single exposure : May cause respiratory irritation.

#### polymethylene polyphenyl isocyanate (9016-87-9)

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

#### polymethylene polyphenyl isocyanate (9016-87-9)

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure (if inhaled).

Aspiration hazard : Not classified

### Fill & Fix Foam EXP

Vaporizer Aerosol

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: Very toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects.
Not rapidly degradable	

<b>dimethyl ether (115-10-6)</b>	
LC50 - Fish [1]	> 4100 mg/l (NEN 6504: Water - Determination of toxicity with <i>Poecilia reticulata</i> , 96 h, <i>Poecilia reticulata</i> , Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 4400 mg/l (NEN 6501: Water - Determination of toxicity with <i>Daphnia magna</i> , 48 h, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value, Lethal)
EC50 96h - Algae [1]	154.9 mg/l (ECOSAR v1.00, Algae, QSAR)

<b>propane (74-98-6)</b>	
LC50 - Fish [1]	49.9 mg/l (96 h, Pisces, Fresh water, QSAR, Estimated value)
EC50 96h - Algae [1]	11.89 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

<b>isobutane (75-28-5)</b>	
LC50 - Fish [1]	27.98 mg/l (ECOSAR v1.00, 96 h, Pisces, Fresh water, QSAR)
EC50 96h - Algae [1]	8.57 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

<b>polymethylene polyphenyl isocyanate (9016-87-9)</b>	
LC50 - Other aquatic organisms [1]	> 1000 mg/l (96 h, Literature study)

<b>alkanes, C14-17, chloro (85535-85-9)</b>	
LC50 - Fish [1]	> 5000 mg/l (Equivalent or similar to OECD 203, 96 h, <i>Alburnus alburnus</i> , Static system, Brackish water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	0.006 mg/l (OECD 202: <i>Daphnia</i> sp. Acute Immobilisation Test, 48 h, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value, GLP)
ErC50 algae	> 3.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, <i>Pseudokirchneriella subcapitata</i> , Static system, Fresh water, Experimental value, GLP)

#### 12.2. Persistence and degradability

<b>dimethyl ether (115-10-6)</b>	
Persistence and degradability	not readily degradable in water.

<b>propane (74-98-6)</b>	
Persistence and degradability	Readily biodegradable in water.

<b>isobutane (75-28-5)</b>	
Persistence and degradability	Readily biodegradable in water.

<b>polymethylene polyphenyl isocyanate (9016-87-9)</b>	
Persistence and degradability	not readily degradable in water.

<b>alkanes, C14-17, chloro (85535-85-9)</b>	
Persistence and degradability	not readily degradable in water.

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 12.3. Bioaccumulative potential

#### dimethyl ether (115-10-6)

Partition coefficient n-octanol/water (Log Pow)	0.1 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

#### propane (74-98-6)

Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

#### isobutane (75-28-5)

Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

#### polymethylene polyphenyl isocyanate (9016-87-9)

BCF - Fish [1]	1 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	10.46 (Calculated, KOWWIN)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

#### alkanes, C14-17, chloro (85535-85-9)

BCF - Fish [1]	6660 – 9140 l/kg (OECD 305: Bioconcentration: Flow-Through Fish Test, 35 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	4.7 – 8.3 (Experimental value, Equivalent or similar to OECD 117)
Bioaccumulative potential	highly bioaccumulative.

### 12.4. Mobility in soil

#### polymethylene polyphenyl isocyanate (9016-87-9)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	9.078 – 10.597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Product adsorbs onto the soil.

#### alkanes, C14-17, chloro (85535-85-9)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	5 – 5.2 (log Koc, Experimental value)
Ecology - soil	Low potential for mobility in soil.

### 12.5. Results of PBT and vPvB assessment

#### Component

alkanes, C14-17, chloro (85535-85-9)	This substance meets the PBT criteria of REACH regulation, annex XIII This substance meets the vPvB criteria of REACH regulation, annex XIII
polymethylene polyphenyl isocyanate (9016-87-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
isobutane (75-28-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
dimethyl ether (115-10-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propane (74-98-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: This material and its container must be disposed of as hazardous waste.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not discharge into drains or the environment.
Additional information	: Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 05 01* - waste isocyanates 16 05 04* - gases in pressure containers (including halons) containing dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID /

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				
<b>14.6. Special precautions for user</b>				
<b>Overland transport</b>				
Classification code (ADR)	: 5F			
Special provisions (ADR)	: 190, 327, 344, 625			
Limited quantities (ADR)	: 1I			

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

### Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

### Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

### Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Fill & Fix Foam EXP	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Fill & Fix Foam EXP ; polymethylene polyphenyl isocyanate ; alkanes, C14-17, chloro	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Fill & Fix Foam EXP ; alkanes, C14-17, chloro	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	dimethyl ether ; propane ; isobutane	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.
56.	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI)
56(a)	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 4,4'-Methylenediphenyl diisocyanate
56(b)	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 2,4'-Methylenediphenyl diisocyanate
56(c)	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 2,2'-Methylenediphenyl diisocyanate
74.	polymethylene polyphenyl isocyanate	Diisocyanates, $O = C=N-R-N = C=O$ , with R an aliphatic or aromatic hydrocarbon unit of unspecified length

Contains a substance on the REACH candidate list in concentration  $\geq 0.1\%$  or with a lower specific limit: alkanes, C14-17, chloro (EC 287-477-0, CAS 85535-85-9)

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

VOC content : 18.16 – 25.49 % (176.02 g/l - 247.03 g/l)

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

##### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878		
2.2		Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Abbreviations and acronyms:	
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Carc. 2	Carcinogenicity, Category 2
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Lact.	Reproductive toxicity, Additional category, Effects on or via lactation
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

# Fill & Fix Foam EXP

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1	H222;H229	On basis of test data
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
Lact.	H362	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 1	H410	Calculation method

Safety Data Sheet (SDS), EU-20212

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.